

TRIAC(Through Hole / Isolated)

TMG8D60F

(Sensitive Gate)


SanRex Triac TMG8D60F is designed for full wave AC control applications. It can be used as an ON/OFF function or for phase control operation.

Typical Applications

- Home Appliances : Washing Machines, Vacuum Cleaners, Rice Cookers, Micro Wave Ovens, Hair Dryers, other control applications
- Industrial Use : SMPS, Copier Machines, Motor Controls, Dimmer, SSR, Heater Controls, Vending Machines, other control applications

Features

- $I_T(RMS)=8A$
- High Surge Current
- Low Voltage Drop
- Lead-Free Package



■ Maximum Ratings

| Symbol | Item | Reference | Ratings | Unit |
|-------------|--------------------------------------|---|----------|------------------|
| V_{DRM} | Repetitive Peak Off-State Voltage | | 600 | V |
| $I_T(RMS)$ | R.M.S. On-State Current | $T_c=89^\circ C$ | 8 | A |
| I_{SM} | Surge On-State Current | One cycle, 50Hz/60Hz, Peak value non-repetitive | 80/88 | A |
| I^t | I^t (for fusing) | | 32 | A ² S |
| P_{GM} | Peak Gate Power Dissipation | | 5 | W |
| $P_{G(AV)}$ | Average Gate Power Dissipation | | 0.5 | W |
| I_{GM} | Peak Gate Current | | 2 | A |
| V_{GM} | Peak Gate Voltage | | 10 | V |
| V_{ISO} | Isolation Breakdown Voltage (R.M.S.) | A.C. 1 minute | 1500 | V |
| T_j | Operating Junction Temperature | | -40~+125 | °C |
| T_{stg} | Storage Temperature | | -40~+150 | °C |
| | Mass | | 2 | g |

■ Electrical Characteristics

| Symbol | Item | Reference | Ratings | | | Unit |
|-------------|---|--|---------|------|------|------------|
| | | | Min. | Typ. | Max. | |
| I_{DRM} | Repetitive Peak Off-State Current | $V_D=V_{DRM}$, Single phase, half wave, $T_j=125^\circ C$ | | | 2 | mA |
| V_{TM} | Peak On-State Voltage | $I_T=12A$, Inst. measurement | | | 1.4 | V |
| I_{GT1}^+ | 1 | | | | 10 | mA |
| I_{GT1}^- | 2 | | | | 10 | |
| I_{GT3}^+ | 3 | | | | — | |
| I_{GT3}^- | 4 | | | | 10 | |
| V_{GT1}^+ | 1 | $V_D=6V$, $R_L=10\Omega$ | | | 1.5 | V |
| V_{GT1}^- | 2 | | | | 1.5 | |
| V_{GT3}^+ | 3 | | | | — | |
| V_{GT3}^- | 4 | | | | 1.5 | |
| V_{GD} | Non-Trigger Gate Voltage | $T_j=125^\circ C$, $V_D=1/2V_{DRM}$ | 0.2 | | | V |
| $[dv/dt]_c$ | Critical Rate of Rise of Off-State Voltage at Commutation | $T_j=125^\circ C$, $[di/dt]_c=-4A/ms$, $V_D=2/3V_{DRM}$ | 10 | | | V/ μ s |
| I_H | Holding Current | | | 15 | | mA |
| R_{th} | Thermal Resistance | Junction to case | | | 3.7 | °C/W |

Trigger mode of the triac

